



Sometimes you want
complicated.

Sometimes you don't.

Lexmark **W840**

Wide-format mono with cutting-edge data security!

Total versatility

Print everything from cards and envelopes to large drafts and designs – and A4 documents as fast as 50 ppm!

PC-free printing

Launch print jobs directly from a USB key, quickly and easily via the direct USB interface and intuitive operating panel.

True peace of mind

Ensure your sensitive documents always stay in the right hands, with state-of-the-art data-security features.

Up to 50 ppm

Direct PDF printing

High capacity
up to 5,100 sheets

We make printing easy

LEXMARK[™]

Lexmark W840/W840n/dn

Boost your productivity with unhindered workflow

Wide-format printing is critical to your business. With the largest maximum-input capacities in its class, the Lexmark W840 delivers unbeatable quality and performance for all your mono-printing needs. You'll also save big on time and money!

Packed with power

Accelerate business with an amazing time-to-first-page of only seven seconds, and output as fast as 50ppm. A robust 625MHz processor and 256MB of standard memory keep your workflow moving like never before!

Simplicity is 'key'

With a USB port directly on the operating panel, users can walk up to the W840, insert a USB key, locate their PDF document on the large LCD screen, and start printing in seconds. It's that easy!

Ensured confidence

Keep prying eyes away from your most sensitive documents with solid transmission security. For even more reassurance, you can count on advanced printing lockout features and 'expiration time' programming.

Easy to grow, easy to save!

The W840's wide range of options provides real scalability for your changing needs. What's more, the high-yield cartridges are easier on your budget, while the automatic-duplex option lets you cut down significantly on paper waste.



*** With special configuration

Models available

W840 - Standalone
W840n - Network
W840dn - Duplex Network

With our innovative solutions and services, we help you **PRINT smarter, MOVE information faster and MANAGE output more efficiently across your enterprise. Ask your local Lexmark representative for more information.**



Technology	Mono laser
Speed	50 ppm
First page out	< 7 seconds
Processor	625 MHz
Memory	Standard: 256 MB Optional: 768 MB
Resolution	True 1200 x 1200 at rated speed 2400 Image Quality
Duty cycle	300K pages per month maximum 10K pages per month average recommended

Standard input	Tray 1: 500 sheets Tray 2: 500 sheets Multipurpose feeder: 100 sheets
Maximum input	6 trays input with a maximum of 5,100 sheets
Output	Standard bin: 500*
Finishing (all optional)	Finisher Output bin 1: 500 sheets Output bin 2: 3,000 sheets Staple, multi-position stapling, hole punch, offsetting
Media supported	Standard: A5, A4, A3, Letter, Executive, JIS B5 Paper size: A5: 148 x 210; A4: 210 x 297; A3: 297 x 420; Letter: 8.5" x 11"; Executive: 184.2 x 266.7; JIS B5: 182 x 257
Connectivity standard	Standalone: USB 2.0 Full Speed, IEEE 1284 Parallel, and Front-side USB Solutions Port Network: USB 2.0 Full Speed, IEEE 1284 Parallel, and Front-side USB Direct Printing, Integrated 10/100 BTX
Network-management software	MarkVision Professional
Compatibility	PostScript Level 3 Emulation PCL 6 Emulation PPDS Migration Tool PDF 1.5 Image Quick (PDF, TIFF, JPEG)
Operating systems supported	Microsoft Windows Microsoft Windows 98, 1st and 2nd edition Windows Me Microsoft Windows NT 4.00 Microsoft Windows NT 4.00 Server Microsoft Windows 2000 Professional Microsoft Windows 2000 Server Microsoft Windows 2000 Advanced Server Microsoft Windows XP Microsoft Windows Server 2003 Apple Macintosh Apple Macintosh System 9.2 Operating System or later with Tri-Port Adapter or MarkNet Print Server Apple Mac OS 9.2 or later with USB Interface or MarkNet Print Server Novell Novell NetWare® 3.x, 4.x, 5.x including full NDS and NDPS support Novell® Distributed Print Services™ (NDPS™) 2.0 or later with Lexmark NDPS IP Gateway Novell NetWare Enterprise Print Services (NEPS) with Lexmark NDPS IP Gateway Linux Caldera OpenLinux 2.3 or later Red Hat Linux 6.0, 7.0 or later SuSE 6.1, 7.0 Linux or later TurboLinux Workstation 3.6 or later
Electronic forms support	Lexmark Forms Card 2, 4, 8, 16MB Flash DIMMs, Lexmark Forms Card Hard Disk
Optional cards	Bar Code Card, IPDS, SCS/Tne Card

Guarantee	Base guarantee: One-year, LexRepair, response time next business day Extended guarantee: 1, 2 or 3 years, LexRepair, response time next business day
Optional services	Installation service, de-installation service, trade-in of old products, hardware and software training
Supplies	Ships with 30K** pages print toner cartridge 30K** pages toner cartridge (aftermarket) 60K pages photoconductor kit Staples Transparencies

Size (H x W x D)	995 x 650 x 650 (base model)	Cost saving & environmental features	30K high-yield print cartridges Selectable "print darkness" levels Print and Hold (verify point) MarkVision alert-driven printer management Power-saver mode
Weight	50.4 kg	Power & electric specifications	Multi-up printing Optional two-sided printing (standard on W840dn) High duty cycle
Acoustics	1 metre average sound pressure 55 db(A) simplex printing 58 db(A) duplex printing 30 db(A) standby		
	1.2 K watts or less while printing 47 watts or less in standby		

* With finisher installed 300 sheets. ** Declared yield value in accordance with ISO/IEC 19752. *** With finishers installed output capacity 3500 sheets.

Specifications are subject to change without notice. Lexmark, Lexmark with diamond design is trademark of Lexmark International, Inc. registered in the United States and or other countries. All other trademarks are the properties of their respective owners.

www.lexmark.com

LEXMARK

INFOLASH • www.infolash.com

PN 8047523