

you can  
**Canon**

## **LaserBase MF3220**



Easy to use, compact and fast Laser multifunctional.

The LaserBase MF3220 is part of the Canon LaserBase range.

The whole LaserBase range consists of: MF8180C, MF6580PL, MF6560PL, MF6550, MF6540PL, MF6530, MF5770, MF5740, MF5730 MF3240 and **MF3220**

**Embargo:** 14<sup>th</sup> April 2006  
**Sales Start Date:** 1<sup>st</sup> June 2006  
**Target Market:** small & medium SOHO

### **Key Features**

- Affordable Laser All-in-One: printer, copier, colour scanner
- Quick first print/copy from standby mode, under 11 seconds
- 20 pages/copies per minute
- 1200 x 600dpi printing (enhanced)
- Colour scanner: 600 x 1200dpi, save to PDF functionality
- USB2.0 Hi-Speed interface
- Flexible paper supply, 250-sheet paper cassette
- All-in-One Cartridge: maintenance free, continuous high quality
- Network printing/scanning with optional Axis 1650 Print Server
- Quiet operation and small footprint

Product Name	Mercury Code	EAN Code	Recommended Retail Price
LaserBase MF3220	0989B025AA	8714574973227	£189.99

#### **What's in the box:**

Main unit, All-in-One cartridge EP-27, power cord, USB cable, starter guide, CD-ROM for driver, CD-ROM user manual, warranty card

New Consumables*	Mercury Code	EAN Code	Recommended Retail Price
Cartridge EP-27	8489A002AA	4960999201719	£65.99

\* For full list of media types see technical specifications

you can  
**Canon**

## LaserBase MF3220



## Technical Specifications

<b>TYPE</b> Machine type Available functions Paper scanning type	Laser flatbed All-In-One Print, Scan and Copy Flatbed
<b>PRINTER FUNCTIONS</b> Printing method Print speed Print resolution Printer Memory Cartridges Yield Smoothing (dpi) Paper capacity Paper Size Maximum printing width Toner saver mode	Mono laser beam printing 20 pages per minute 600 x 600 dpi 32MB EP-27 Cartridge 2500 pages (Based on ISO/IEC19752) 1200 x 600 dpi 250 sheets A4, LTR, LGL, Envelope (COM10, Monarch, DL, ISO-5) 216mm Yes (Cartridge yield – approx 3125 pages)
<b>SCANNER FUNCTIONS</b> Scanner type Automatic document feeder Scanner resolution Colour scanning depth Greyscale gradation Compatibility Effective scanning width OCR Software bundled Other features	Colour CIS No 600 x 1200dpi 24bit/24bit (in/out) 8bit TWAIN, WIA 216mm Yes Dust and scratch removal, Scan to PDF, Scan to Email
<b>COPIER FUNCTIONS</b> Copy resolution Copy modes Copy speed Multiple copy Zoom ratio First copy output time (FCOT) Other features	600 x 600 dpi Text, Photo, Text & Photo 20 copies per minute Up to 99 copies 50-200% Less than 11 seconds 2-on-1 Copy, First warm up time less than 8 secs
<b>PC INTERFACE AND SOFTWARE</b> Interface type Software Supported OS PC FAX ( TX) PC FAX ( RX) Printer drivers Scan drivers Scan to E mail Other features Number of languages (Windows 98/ME/2000/XP) Bundled Software Network option	USB 2.0 Hi-Speed Windows 98/Me/2000/XP No No Yes Yes Yes Scan to PDF, Scan to OCR, Scan to Email English, French, German, Italian, Spanish, Dutch, Polish, Russian Presto!PageManager, ScanSoft OmniPage SE Yes (AXIS 1650)

<b>GENERAL SPECIFICATIONS</b> Number of language (LCD message)	16 languages (English, German, French, Spanish, Italian, Swedish, Norwegian, Dutch, Finnish, Danish, Portuguese, Slovenian, Czech, Hungarian, Russian, Turkish)
Dimensions with trays (W x D x H)	449mm x 487mm x 369mm
Dimensions without trays (W x D x H)	449mm x 546mm x 369mm
Installation space including trays (WxD)	449mm x 462mm
Weight	Approx. 11.kg
Power Source	AC 200-240V, 50-60Hz
Consumption	Max: Approx. 700w Standby: Less than 8W Energy Save: approx 5W
Acoustic Noise Levels	Standby: 30dB(A) max Copy: under 56dB(A) max
<b>SYSTEM REQUIREMENTS</b> Software Operating System	Windows 98/Me/2000/XP 100MB of available hard disk space (150MB is recommended) 64MB RAM (128MB is recommended) 128MB RAM (256MB is recommended) for USB 2.0 Hi-Speed
<b>OPTIONS</b> Items	AXIS 1650 Network Print Server

All data is based on Canon's standard testing methods.  
This leaflet and the specifications of the product have been developed prior to the date of product launch.  
Final specifications are subject to change without notice.  
™ and ®. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.



Automatic Image Refinement

