

# T2150/T2150S/T2250



## Reliable, Fast Transaction Printing

The dependable T2150 and T2250 offer class-leading performance. Flat push tractors drive forms through a straight paper path, resulting in delivery of invoices, shipping bills, labels, and statements time after time. At up to 750 characters per second and with workloads to 26,000 pages per month, the T2150 and T2250 are ideal for tough, transaction printing. The T2150 and T2250 can be optionally configured with up to three input tractors and the T2150S model boasts a built in cutter device.

From the small 80-column footprint of the T2150 to the 136-column capacity of the T2250, their rugged design and quiet operation equip them for the warehouse, the shipping dock or the front desk. Back room durability combined with front-office 24-wire print quality and a variety of automated performance features make the T2150 and T2250 a serious solution for demand document pricing.

### Exceptional Features

- Print speeds up to 750 characters per second
- 26,000 pages per month workload
- 80-column (small footprint) or 136-column configurations available
- 15 industry standard bar codes resident including POSTNET
- 24-pin print head produces excellent print quality

### Versatile Forms Handling

- Load up to three forms at once
- Straight paper path for jam-free operation
- Load up to 6-part forms on front tractors
- Automatic gap adjustment and quick-tear

### Ease of Use

- Simple to operate control panel
- Paper park for easy switching between forms
- Quick and easy installation

Consumables

Ink Jet Printers

Laser Printers

Line Matrix Printers

**Serial Matrix Printers**

# T2150/T2150S/T2250

## Serial Matrix Printers

# Features & Specifications

<b>Printing Technology</b>	Serial impact dot matrix
<b>Print Method</b>	Bi-directional
<b>Print Speed</b>	10 CPI: Draft: 500 cps; NLQ: 180 cps; LQ: 90 cps 12 CPI: Draft: 600 cps, NLQ: 220 cps, LQ: 110 cps 15 CPI: Draft: 750 cps; NLQ: 135; LQ: 135 cps
<b>Print Head</b>	24-wire
<b>Parameter Selections</b>	Front panel menu (32 character LCD) and host programmable (3 separate menu configurations can be stored for access through the interface)
<b>Workload</b>	26,000 pages per month
<b>Bar Codes</b>	Code 2/5, Code EAN 8, Code EAN 13, Code UPCA, Code UPCE, Code Delta-Distance; Code 39, Codabar, Code BCD matrix, Code 11, Code MSI/modified Plessey, Code 128, Code 128 EAN, POSTNET, LCP
<b>Fonts</b>	Std: Draft, Copy Draft; NLQ and LQ: Courier, Roman, San Serif, Cyrillic, OCR A/B, 15 Bar codes & scaleable LCP font (Accepts downloadable fonts in Epson® and IBM® XL24 format)
<b>Printing</b>	
<b>Character Sets</b>	256 characters, 20 international sets, IBM® PC and Epson®
<b>Graphic Resolution</b>	Maximum: 360 x 360 dpi
<b>Character Density</b>	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
<b>Characters Per Line</b>	T2150/T2150S: 80 at 10 cpi, 96 at 12 cpi, 120 at 15 cpi, 136 at 17.1 cpi, 160 at 20 cpi T2250: 136 at 10 cpi, 163 at 12 cpi, 204 at 15 cpi, 232 at 17.1 cpi, 272 at 20 cpi
<b>Line Density</b>	2, 3, 6, 8, 12 lpi
<b>Copies</b>	Orig. +5 (front push tractors) without jamming; 3 forms at once and autoswitch between forms without operator intervention
<b>Paper Handling</b>	Paper Width: Std: Front tractor and manual front insertion (cut sheets) T2150/T2150S: 3-10"; T2250: 3-16.5" 3" - 16.5" width; 3" - 22" length Std: Friction and push tractor, front feed (straight path for continuous forms and labels), auto paper load, auto quick tear, auto view, full paper parking, auto-gap adjustment (for forms thickness) Opt: Supplemental push tractors (front and/or rear), single-bin automatic sheet feeder**
<b>Emulations</b>	Std: MTPL* (including 15 resident bar codes and LCP), IBM® Proprinter XL24, Epson® LQ-2550
<b>Interfaces &amp; Connectivity</b>	Std: Bi-directional Centronics Parallel and RS-232 Serial (auto-switching); Optional: RS-422 Serial Buffer Size: 64K
<b>Physical Specifications</b>	T2150/T2150S: 16.7" x 11.8" x 15.7"; 29 lbs.; T2250: 23.6" x 11.8" x 15.7"; 35 lbs. Acoustic Level: 53 dB(A)
<b>Operating Environment</b>	Power Requirements: AC 120V/60 Hz or 220-240V/50 Hz Consumption: 40 watts (operating); 15 watts (standby)
<b>Reliability</b>	MTBF: 10,000 hours
<b>Ribbon</b>	Cassette: T2150/T2150S: 3.6 million characters; T2250: 5.0 million characters
<b>Options</b>	Supplemental push tractors, auto sheet feeder, DEC LA75, RS-422 I/O, Ethernet 10/100
<b>Warranty</b>	One Year



T2150/T2150s



T2250



BSEN ISO 9001: 1994  
Certificate No. FM  
28149



4500 Daly Drive, Suite 100  
Chantilly, VA 20151

T 800.436.4266  
www.tallygenicom.com

Tally and TallyGenicom are registered trademarks of TallyGenicom, L.P. All other company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.