

T2265 & T2280 Dot Matrix Printers



Incredible performance

The T2265 and T2280 models are testament to Tally's commitment to this technology, with print speeds of up to 900cps and 1100cps respectively they are truly the leaders of the pack. This combined with a wide range of fonts and industry standard barcodes, automatic sheet feeders and additional tractors, plus network connection options to PC LAN, IBM mainframe and AS400, allows users to make full use of this most powerful range of printers in business critical printing applications.

Key features

- High quality 24 pin printhead
- Straight through paper path
- Easy to use front panel
- IBM Proprinter and Epson emulations for easy connection on a wide variety of hosts and applications
- Automatic top of form for easy alignment
- Automatic paper loading
- Zero tear off for no wasted forms
- Paper park facility for easy switching between forms
- Automatic sheet feeder and cutter options
- Colour models available
- LAN, IBM AS400/mainframe connectivity options
- Includes full support for all versions of Windows and SAP R-3

Key applications

- Delivery notes
- Invoices
- Picking lists
- Standard listings
- Labels
- Barcodes

Product	Part Number
T2265 printer, with parallel and serial interface (UK)	917401
T2265C printer, with parallel and serial interface, colour (UK)	917404
T2280 printer, with parallel and serial interface (UK)	917801
T2280C printer, with parallel and serial interface, colour (UK)	917804
T2280-2T printer, with parallel and serial interface and second tractor (UK)	917812
T2265 printer, with parallel and serial interface (international)	917400
T2265C printer, with parallel and serial interface, colour (international)	917403
T2280 printer, with parallel and serial interface (international)	917800
T2280C printer, with parallel and serial interface, colour (international)	917803
T2280-2T printer, with parallel and serial interface and second tractor (international)	917810
Program Packs	
DEC LA75 emulation	048047
MT460D emulation	048056
MT50 emulation	048059
Interfaces	
Interface-ethernet 10/100	048254
Interface-20 mA current loop (TTY)	047250
Interface-RS422	047251
HostCom pocket twinax SCS (matrix)	043534
HostCom pocket coax SCS (matrix)	043533
Serial adapter cable 9 to 25 way	RAC1286-1
Options	
Automatic sheet feeder + 2 bins	061905
Cutting device	061907
Enclosed pedestal	061910
Additional push tractor	061062
Automatic Sheet Feeder - Front	061906
Consumables	
Fabric ribbon-black (20 million characters)	060097
Fabric ribbon-red, black, black, black (2/6/6/6 million characters)	060099
Fabric ribbon-cyan, magenta, yellow, black (2/2/2/2 million characters)	060098
Fabric ribbon-red, blue, green, black (2/2/2/2 million characters)	060100

Specification

Printer models	T2265 - mono, 136 column, 24 pin T2265C - spot colour, 136 column, 24 pin T2280 - mono, 136 column, 24 pin T2280C - spot colour, 136 column, 24 pin T2280-2T - mono, 136 column with 2nd (rear) tractor
Workload	T2265 - 2000 pages per day T2280 - 2500 pages per day
Advanced automatic features	Automatic gap adjustment (AGA), Automatic paper loading, Automatic paper parking, Automatic view and tear, Automatic paper switching, Automatic paper path monitoring (paper motion sensor), Automatic interface switching
Print speed - max	T2265 - 900cps (@15cpi) T2280 - 1100cps (@15cpi)
Print speed - std	T2265 - 650cps (@10cpi) T2280 - 800cps (@10cpi)
Throughput (ECMA 132)	See table
Character pitch	10, 12, 15, 17.1, 20cpi
Line pitch	2, 3, 4, 6, 8, 12pi
Graphics resolution	Up to 360 x 360dpi
Fonts	Draft, copy draft, courier, roman, sans serif, prestige, script, OCR A & B, 19 Barcodes and scaleable LCP Font, range of Arabic
Paper handling - std	Push tractors with paper parking and AGA 2nd rear push tractor - T2280-2T only, 1+1 copies Cut sheet front insertion with AGA, 1+3 copies
Paper handling - opt	2nd front tractor (user installable) Dual bin automatic sheet feeder* (190 sheets per bin), face down output bin*, paper cutting device, paper pedestal Front feed-190 sheets)
Paper types	Continuous forms 60 - 120gsm Cut sheet - 100 to 420mm wide, 60 - 90gsm
Multi-part stationery	1+6 copies (1+1 for rear tractors of T2280-2T)
Interfaces - std	Serial RS-232 and bi-directional parallel with 128Kb buffer
Interfaces - opt	Serial RS-422, current loop (TTY 20mA), Ethernet 10/100 BaseT, Tally HostCom pocket adapters: Coax SCS Matrix or twinax SCS matrix
Emulations -std IBM proprinter XL24e	MTPL + barcode / LCP, Epson LQ (Esc P/2),
Emulations - opt contextual Arabic	MT50, MT460, DEC LA75, (program packs),
Noise level (ISO 7779)	53dB(A)
Power supply	120 / 230-240V 70W printing
Print head life	500 million characters
Weight	19Kg
Dimensions	277(h) x 623(w) x 430(d)mm
MTBF	10,000 hours
NOTE*	*The dual bin sheet feeder and face down output bin are unsuitable for use with the T2280-2T

NB: Paper is a highly variable medium, and should be tested prior to purchase.

The quoted consumable life is the average for the printer when used under normal operating conditions.

For barcode and OCR applications it is recommended that your optical readers are tested with print samples supplied by Tally prior to purchase.



UK 0800 652 4557, Int +44 1256 481 502, or www.tally.co.uk