

you can
Canon

LASER SHOT LBP3460



The complete high-speed, high quality laser printing solution.

The LaserShot LBP3460 is part of the Canon LaserShot range.

The whole range consists of: LBP5200, LBP5000, **LBP3460**, LBP3300, LBP3200, LBP3000 and LBP2900.

Embargo Date: 15th January 2006
Sales Start Date: March
Target Market: large SOHO

Key Features

- 33 pages per minute heavy-duty Laser Printer
- PCL 5e/6 & UFR II* supported for maximum compatibility
- Network ready (TCP/IP) for sharing printer resources
- Built-in duplex unit to provide double-sided printing
- No warm-up time and first print ready in approx. 8 seconds
- Print quality: 600 x 600 dpi (2400 x 600 dpi equivalent)
- Maintenance-free All-in-One cartridge
- 250-sheet cassette and 100-sheet multi-purpose tray plus optional 500-sheet cassette
- USB2.0 Hi-Speed connection between printer and PC
- Stylish, space-saving design with full frontal operation

* Canon's own printer language

Product Name	Mercury Code	EAN Code	Recommended Retail Price
LaserShot LBP3460	0571B012AA	871457966083	£779 / €1125

What's in the box:

Main Unit, Toner Cartridge 710, CR-ROM for driver, CD-ROM User Manual, getting started guide, panel cover, power cord, warranty card

Optional Accessories	Mercury Code	EAN Code	Recommended Retail Price
Paper Cassette	0941B002AA	4960999329154	TBC

New Consumables*	Mercury Code	EAN Code	Recommended Retail Price
Cartridge 710	0985B001AA	4960999322247	TBC
Cartridge 710H	0986B001AA	4960999322261	TBC

* For full list of media types see technical specifications

you can
Canon

LASER SHOT LBP 3460



Technical Specifications

ENGINE	
Printing speed	Mono 33 pages (A4)
Printing method	Electrophotographic printing using laser beam printing
Fixing method	On-Demand fixing
Resolution	600 x 600 dpi (2400 x 600 dpi with image refinement)
Warm-up time	0 seconds (9 seconds or less when the printer is on)
First print	approx 8 seconds
Toner cartridge	First (included with printer) Black 6.0K pages, Replacement: either Black 6.0 K pages or 12.0K pages (high capacity)
Toner Save	Yes
Paper Input (standard)	250-sheet cassette/100-sheets multi-purpose tray
Paper input (Option)	500-sheets x1 (Maximum paper capacity 850 sheet)
Paper output	Face down: 250 sheets, Face up: 50 sheet
Paper size	A4, B5, A5, Legal, LTR, Executive, Envelope B5/C5/COM10/DL/Monarch, Index Card Custom Paper (width 76.2 - 215.9mm, length 127.0 - 355.6mm)
Duplex printing	Yes (built-in type as standard)
Power requirements	220-240V(±10%) 50/60Hz (±2Hz)
Power consumption	1300W or less (max power consumption) Approx. 572W (Average during operation) Approx. 6W (Average during standby)
Noise level	Background noise level 0.4 dB or less during standby Sound pressure level: 52dB[A] or less (during operation)
Dimensions (W x D x H)	445 x 410 x 273 (mm)
Weight (without cartridge)	Main print Unit approx 1.6 kg (Without CRG)
Cartridge/Drum weight	CRG approx 1.3kg (cartridge 710/6.0K yield) Approx 1.6 kg (cartridge 710H/12.0K yield)

Operating environment	Temperature: 10 to 30°C (50 to 86°F) Humidity 10 to 80%RH (no condensation)
Storage environment	Temperature: 0 to 35°C (32 to 95°F) Humidity 35 to 85%RH (no condensation)
Energy Star Compliant	Yes
CONTROLLER HARDWARE	
Smoothing technology	AIR (Automatic Image Refinement) 2400 x 600 dpi equivalent
CPU	R4000-333MHz
RAM (Standard)	64MB
RAM (Optional)	Expandable up to 320MB by installing an optional RAM module (64MB, 128MB and 256MB optional RAM ready)
ROM (Optional)	optional ROM DIMM for Netware & BarDIMM
Interface (Standard)	USB 2.0 High Speed/Full Speed
Interface (Optional)	10Base-T/100Base-TX
CONTROLLER SOFTWARE	
PDL (Standard)	PCL5e/PCL6 and UFR II
Supported PC OS	Windows NT4.0/98/Me/2000/XP/Server2003/ Netware (Option)/Linux
Mac Compatible	Yes (Mac OS 10.2.8 or higher - English only)
Supported Canon Application	Netspot Device Installer/Netspot Console Remote UI/Netspot Accountant/RDS
Other features	
Font (Standard)	PCL; 80 Scalable fonts, 10 Bitmap fonts
Font (Optional)	BarDIMM (Optional)



Automatic Image Refinement

