



Embargo date: 19th August 2010
Available to order from: September 2010
Launch Weekend: 8th October 2010
Target Market: Advanced / Home / Office

Key Features:

- Advanced Photo All-In-One with superior photolab-quality and 5 Single Inks
- Wi-Fi b/g/n connectivity for sharing over high-speed networks
- ISO ESAT 11/9.3 ipm Mono/Colour, 10x15cm borderless photo in approx. 20 sec
- Print high quality images from your movies with Full HD Movie Print
- Auto Duplex print, Direct Disc print & 2 way paper feeding
- Take control of your web printing with Easy-WebPrint EX
- Intuitive interface with 6.0cm TFT display
- CREATIVE PARK PREMIUM when used with genuine inks
- Auto Photo Fix II and Auto Document Fix automatically correct and enhance images and documents
- ChromaLife100+ for long lasting, beautiful photo

Wireless, high quality, feature-rich All-In-One for the home.

The PIXMA MG5250 is an advanced, feature-rich All-In-One with Wi-Fi, Auto Duplex print and Direct Disc print. Get to the function you need more quickly with an intuitive interface & 6.0cm TFT display.

The PIXMA MG5250 is part of the PIXMA Photo All-In-One range.

The Canon PIXMA Photo All-In-One range consists of: PIXMA MP280, PIXMA MP495, PIXMA MG5150, **PIXMA MG5250**, PIXMA MG6150 and PIXMA MG8150.

Product Name	Mercury Code	EAN Code	Recommended Retail Price
PIXMA MG5250	4502B008AA	4960999667669	£149 / €179

What's in the box: PIXMA MG5250 All-In-One, Power cord, Ink tanks (PGI-525PGBK, CLI-526BK, CLI-526C, CLI-526M, CLI-526Y), Multilingual set up guides, Set up software and User's manual CD, Warranty sheet.

Model Name	Mercury Code	EAN Code	Recommended Retail Price
PGI-525PGBK	4529B001AA	4960999669922	£13.99 / €17.99
CLI-526BK	4540B001AA	4960999670027	£11.99 / €14.99
CLI-526C	4541B001AA	4960999670034	£11.99 / €14.99
CLI-526M	4542B001AA	4960999670041	£11.99 / €14.99
CLI-526Y	4543B001AA	4960999670058	£11.99 / €14.99
CLI-526 C/M/Y Multipack	4541B006AA	8714574554457	£31.99 / €39.99
PGI-525PGBK Twin Pack	4529B006AA	8714574554464	£23.99 / €29.99

Technical Specifications

TYPE Available Functions	Print, Scan & Copy. Camera, Memory Card, Mobile phone and direct disc printing.
PRINTER FUNCTIONS Print Resolution Print Engine Photo Lab Quality Speed Mono Print Speed Colour Print Speed Ink Cartridge Configuration Black Ink Tank Life Colour Ink Tank Life Media Type Media Input Media Size Media Weight Direct Disc Printing Two Sided Printing Borderless Printing Compatible Memory Cards Card Direct Print Functions Card Direct Print Enhancements Print Driver Features	Up to 9600 ³ x 2400 dpi Inkjet 5-ink with minimum 1 pl droplet size and FINE print head Borderless 10 x 15cm: Approx. 20 seconds ESAT: Approx. 11.0 ipm ESAT: Approx. 9.3 ipm Single Ink technology - 5 separate ink tanks (PGI-525PGBK, CLI-526BK, CLI-526C, CLI-526M, CLI-526Y) Black: 341 pages (PGI-525PGBK), 3005 pages* (CLI-526BK) ² Black: 3800 photos* (PGI-525PGBK), 660 photos* (CLI-526BK) ² *Estimated Supplemental Yield Cyan: 520 pages (CLI-526C), Magenta: 500 pages (CLI-526M), Yellow: 515 pages (CLI-526Y) ² Cyan: 207 photos (CLI-526C), Magenta: 204 photos (CLI-526M), Yellow: 202 photos (CLI-526Y) ³ Plain Paper, Envelopes, Photo Paper Pro Platinum (PT-101), Photo Paper Plus Glossy II (PP-201), Photo Paper Plus Semi-gloss (SG-201), Glossy Photo Paper "Everyday Use" (GP-501), Matte Photo Paper (MP-101), High Resolution Paper (HR-101N), T-shirt Transfer (TR-301), Photo Stickers (PS-101), Rear Tray: Max. 150 sheets Front Tray: Max. 150 sheets Direct Disc Print Tray: 1 printable Blu-Ray [®] Disc, DVD or CD Rear Tray: A4, B5, A5, Letter, Legal, Envelopes (DL or Commercial 10), 10 x 15cm, 13 x 18cm, 20 x 25cm. Cassette: A4, B5, A5, Letter Rear Tray: Plain paper 64 to 105 g/m ² and supported Canon special media up to approx. 300 g/m ² . Cassette: Plain paper: 64 to 105 g/m ² . Available as Standard Automatically selectable using plain paper in A4, B5, A5 & Letter sizes Yes (A4, Letter, 20 x 25cm, 13 x 18cm, 10 x 15cm) USB Flash Memory, CompactFlash, Microdrive, Memory Stick, Memory Stick Pro, Memory Stick Duo, Memory Stick PRO Duo, SD Memory Card, SDHC Memory Card, MultiMedia Card (Ver.1), and MultiMedia Card Plus (Ver.1), xD-PictureCard [™] , xD-PictureCard Type M [™] , xD-PictureCard Type H [™] , Memory Stick Micro [™] , RS-MMC [™] , MMCmobile Card [™] , mini SD Card [™] , micro SD [™] , mini SDHC Card [™] and micro SDHC [™] Select photo, print all photos, label print, photo index print (standard & contact print), calendar print, ID photo print, print job queuing, Direct Disc Print Auto Photo Fix II, Red-eye correction, noise reduction, face brightener, crop image Collate, multiple page per sheet print, booklet print ¹ , poster print ² , scaled print ³ , fit-to-page print, Photo Noise Reduction, photo effects
SCANNER FUNCTIONS Scanner Type Film Scanning Scanner Resolution Optical A4 Scan Speed (reflective) Colour Scanning Depth Halftone/Greyscale Compatibility Effective Scanning Width OCR Bundle Scan Methods & Enhancements	Flatbed CIS colour scanner n/a Up to 2400 x 4800 dpi Approx. 17 seconds ⁵ 48 bit input / 24 bit output (RGB each 16 / 8 bit) 16 bit input / 8 bit output TWAIN / WIA A4/LTR (216x297mm) Yes (MP Navigator EX) Scan jpeg, compact PDF or normal PDF to memory card or USB memory, attach to email, Push-scan, Auto Scan Mode, Auto Document Fix, PDF file creation/editing/password security*, Stitch Assist*, Correct document orientation, Prevent show through, Correct slanted documents, Photo corrections (Fading correction, Grain correction, Reduce dust and scratches, Backlight correction, Auto Tone), Gutter Shadow Correction, Text (OCR) * Function with MP Navigator EX

COPIER FUNCTIONS Colour/Photo Copy Copy Speed Colour Document Multiple Copy Zoom Copy functions & enhancements	Yes FCOT: Approx. 15 secs. max.99 copies 25 - 400% in 1% increments and preset ratios Borderless copy, two-sided copy, 2-on-1 and 4-on-1 copy, frame erase copy, Disc label copy, Auto Photo Fix II, fade restoration
INTERFACE AND SOFTWARE Display Type & Size Interface Type - PC / Mac Interface Type - Interface Type - Non PC Supported Operating System Operating System Requirements Software Included	6.0cm colour TFT display with Quick Operation Hi-Speed USB (B Port), Bluetooth Ver.2.0 maximum speed 1.44Mbps (Option, HCRP) (with optional Bluetooth Unit BU-30) Wi-Fi: IEEE802.11b/g/n Set-up: WCN, WPS (Push-Button Configuration, PIN code method), Security: WPA-PSK, WPA2-PSK, WEP64/128bit, Administration password Over Wi-Fi: Android devices ¹ , iPhone [®] , iPod touch [®] , iPad [®] , Sony Playstation 3 Bluetooth Ver.2.0 maximum speed 1.44Mbps (Option, JPEP only, OPP, BIP) (with optional Bluetooth unit BU-30) Photo printing via PictBridge Windows 7 (32 and 64bit), Windows Vista (32 and 64bit), Windows XP SP2, SP3 Mac OS X v.10.4.11 - 10.6 Windows 7: 1 GHz or faster cpu, 1 GB RAM (64 bit requires 2 GB RAM) Windows Vista (32/ 64 bit): 1 GHz or faster cpu, 512MB RAM Windows XP SP2,3: 300 MHz or faster cpu, 128 MB RAM Browser: Internet Explorer 6 or higher CD-ROM Drive Display: 1024 x 768 or better ¹⁰ Mac OS 10.6: Intel Processor, 1 GB RAM Mac OS 10.5: Intel or PowerPC Processor (G4, G5, 867 MHz or faster) Mac OS 10.4.11: Intel or PowerPC Processor (G5, G4, G3), 256 MB RAM Browser: Safari 3 or higher CD-ROM Drive Display: 1024 x 768 or better ¹⁰ Canon Multifunctional drivers, Canon MP Navigator EX (including OCR and PDF file creation), Canon Easy-PhotoPrint EX with HD Movie Print function, Canon Easy-WebPrint EX, and Canon Solution Menu EX
GENERAL FEATURES Dimensions (W x D x H) Number of language (LCD) Temperature Range Humidity Acoustic Noise Levels Weight Power Source Power Consumption	455 x 368 x 160mm 22 Languages selectable: Japanese, English, German, French, Italian, Spanish, Dutch, Portuguese, Norwegian, Swedish, Danish, Finnish, Russian, Czech, Hungarian, Polish, Slovenian, Turkish, Simplified Chinese, Greek, Traditional Chinese, Korean Operating environment: 5° - 35° C Operating humidity: 10 - 90%RH (no condensation) Printing (when feeding from rear tray): Approx. 47.5 dB(A) When printing ISO/115-SCID N2 pattern on 10x15cm Photo Paper Plus Glossy II using default settings Approx. 8.1 kg AC 100-240V, 50/60Hz Standby: Approx. 1.6 W (when scanning lamp is off), Off: Approx. 0.4 W, Copying: Approx 21W ¹¹

Footnotes

- Ink droplets can be placed with a minimum pitch of 1/9600 inch
- Declared yield value in accordance with ISO/IEC 24711. Values obtained by continuous printing.
- When printing Canon standard patterns continuously with the default settings on 10x15cm Photo Paper Plus Glossy II using Windows 7 printer driver in borderless printing mode and Windows 7 Home Premium's Windows Photo Viewer. Declared yield value determined based on Canon standard method referring to ISO/IEC 24711.
- Using recommended adapter - not supplied.
- Available in Windows driver only
- Color document scan speed is measured with ISO/IEC 24735 Annex C Test Chart A.
Scan speed indicates the time measured between pressing the scan button of the scanner driver and the on-screen status display turns off. Scan speed may vary depending on system configuration, interface, software, scan mode settings and document size etc.
- When connected to a device running Android 1.6 or higher OS over an existing infrastructure mode Wi-Fi network. Only available in certain countries / regions.
- When connected over an existing infrastructure mode Wi-Fi network. Canon iEPP application available as free download from Apple App Store. Compatible with iPhone OS 2.2.1 or higher. Only available in certain countries / regions.
- Internet Explorer 7 or higher required for Easy-WebPrint EX. Operation can only be guaranteed on a PC with Windows 7, Windows Vista or Windows XP pre-installed
HD Movie Print for Windows requires 2.6 GHz or faster processor, 1GB RAM and Canon ZoomBrowser EX 6.5 or later.
- HD Movie Print for Mac OS requires Intel processor and Canon ImageBrowser 6.5 or later software.
- When copying ISO/115-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.

Standard disclaimers

All specifications subject to change without notice. Borderless 10x15cm photo lab quality print speed based on default driver setting using ISO/115-SCID N2 on Canon Photo Paper Plus Glossy II media. Document print speed (ipm) on plain paper is measured based on the averages of the office category test ISO/IEC 24734. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used and does not take into account data processing time on host computer. FCOT on plain paper is measured based on the test standard of ISO/IEC 24735 annex D. Ink yield may vary depending on texts/photos printed, applications software used, print fonts mode and type of paper used. For yield information see www.canon-europe.com/ink/yield

All brand and product names are trademarks of their respective companies.

Microsoft, Windows and the Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries.

For more information on ChromaLife100[™] please visit www.canon-europe.com/chromalife100.