

# T2250

## Fast, reliable class leading printers



*Tally*

The T2150 and T2250 are highly featured, reliable and stylish machines. Performance and workload, ergonomics, maintainability, excellent price - everything has been incorporated to ensure they are the only acceptable choice for the customer.

Continuous and cut forms are fed at the front for quick and easy loading. This ensures a straight path for the forms resulting in reliable paper transportation, even on 6-part stock. Loading paper is easier. The operator does not have to fumble over or around the printer to gain access to rear located tractors. If 'tear at top of form' is inadequate for your application, the T2150S features a cutting device which separates forms automatically.

- **Print speeds up to 750 cps**
- **26,000 pages per month workload**
- **136 columns**
- **24 pin print head produces excellent print quality**
- **Automatic gap adjustment and quick tear**
- **Straight through paper path for easy forms loading**
- **Parallel and Serial interfaces standard**
- **LAN, IBM AS400/iSeries, Mainframe optional**

User intervention is kept to a minimum with a suite of features designed to ensure the products run at optimum reliability and performance.

The product is at home in the computer room, data processing room, or in the office. An unobtrusive 52dBA acoustic rating results in a printer, which is half as quiet, compared with many competitive models.

Available Configuration:

T2250 Standard Product  
LA550W DEC Compatible Version  
T2250 IGP with IGP/JPL Support

SERIAL MATRIX  
PRINTERS

MOBILE  
PRINTERS

THERMAL  
PRINTERS

LINE MATRIX  
PRINTERS

LASER  
PRINTERS

CONNECTIVITY

CONSUMABLES

SERVICE

# T2250





<b>Print Speed</b>	>750cps 15cpi, >600cps 12cpi, >500cps 10cpi
<b>Printhead Life</b>	400 million characters
<b>Memory</b>	128Kb
<b>Standard Connectivity</b>	Parallel (bi-directional) and serial RS232
<b>Optional Connectivity</b>	Serial current loop (20mA), Ethernet 10/100 Base T, USB Parallel Adapter, HostCom pocket coax matrix for IBM mainframe HostCom pocket twinax for AS400, iSeries, System 3X
<b>Standard Emulation</b>	IBM proprinter XL24, Epson LQ2550, Tally MTPL + barcode + LCP, <b>IGP Version:</b> IGP/PGL, Code V, MT660, Printronix P6000, HP2564C
<b>Optional Emulation</b>	DEC LA75; MT50 (Diskette and manual program packs)
<b>Fonts</b>	HS draft (sans serif), draft (sans serif), Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B*, 19 barcodes and large character printing. Range of Arabic fonts (Arabic model)
<b>Consumables</b>	Ribbon: 5 million characters
<b>STD Paper Handling</b>	Push tractors with paper parking and automatic gap adjustment (AGA). Cut sheet front insertion with AGA
<b>Paper Type</b>	Continuous forms, cut sheets
<b>Paper Weight</b>	Continuous forms 60-120gsm; Cut sheet 80-120gsm
<b>Paper Size</b>	420mm max
<b>Physical Weight</b>	Approximately 11Kg
<b>Physical Size</b>	(HxWxD): 300x600x295mm
<b>Power Voltage</b>	230V
<b>Power Consumption</b>	40W printing
<b>Workload</b>	26,000 pages per month
<b>Number of Copies</b>	Up to 6 part forms
<b>Temperature</b>	+10° to +35°C
<b>Humidity</b>	20% to 80%
<b>Acoustic</b>	53dB(A)
<b>Warranty</b>	2 years, on-site

**DASCOM GB Limited**  
ViewPoint, Basing View,  
Basingstoke, Hampshire RG21 4RG  
Tel: +44 (0) 1256 481481  
Fax: +44 (0) 1256 481400

[www.dascom.com](http://www.dascom.com)

All company and product names are trademarks or registered trademarks of their respective owner. Specifications are subject to change without notice.

Copyright © 2009 DASCOM Europe GmbH  
Ver. 1.0  
Printed Date: 01.04.10

SERIAL MATRIX PRINTERS   
MOBILE PRINTERS   
THERMAL PRINTERS   
LINE MATRIX PRINTERS   
LASER PRINTERS 